
THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT · THEAVIATIONPOINT.COM

ASNA0341 — Maxibolt type, titanium, 100° countersunk

Blind bolt, Maxibolt type, titanium, 100° countersunk head, as the ASNA standard gives it: part numbers by diameter and grip, the hole and the drill, the tools and the inspection limits.



Engineering drawing · dimensions in inches and millimetres

Specification

Item	Value
Type	Blind bolt, pulled stem with locking collar
Material	Titanium (the letter T; the alloy is not named in the standard data)
Locking	Pulled stem with a locking collar; the collar must never stand beyond the stem after the break
Finish	Not stated in the standard data
Status	Reference data transcribed from the standard, units marked row by row. Check the issue of the standard in force before design use.

Dimensions by size

Dimension, inch first (mm after)	-04	-05	-06	-08
Nominal Ø (code)	1/8 in (0.125 in; 3.17 mm)	5/32 in (0.156 in; 3.97 mm)	3/16 in (0.188 in; 4.76 mm)	1/4 in (0.250 in; 6.35 mm)
Body Ø	0.128 in (3.25 mm)	0.163 in (4.14 mm)	0.198 in (5.03 mm)	0.259 in (6.58 mm)
Hole †	0.129–0.132 in (3.28–3.35 mm†)	0.164–0.167 in (4.16–4.24 mm†)	0.199–0.202 in (5.05–5.13 mm†)	0.260–0.263 in (6.60–6.68 mm†)
Drill (chart)	#30 (0.1285 in; 3.26 mm), just under the minimum: gauge the hole	#19 (0.1660 in; 4.22 mm)	#7 (0.2010 in; 5.11 mm)	G (0.2610 in; 6.63 mm)
Max csk Ø †	0.229 in (5.82 mm†)	0.334 in (8.48 mm†)	0.387 in (9.83 mm†)	0.508 in (12.90 mm†)

Units: no mark = printed in mm and stated by the standard. † = printed with no unit; the inch value is our conversion, reading the figure as mm. Nominal Ø is our reading of the inch code (1/32 in for diameters, 1/16 in for grips). Drill: from the site drill chart, inside the hole range except code 04, where the chart's #30 (0.1285 in) is just under the printed minimum (a drill cuts slightly oversize): gauge the finished hole.

Part numbers

-04 · 1/8 in nominal 16 part numbers

Part no.	Grip, in (mm printed)
ASNA0341T0401	0.093–0.157 (2.36–3.99)
ASNA0341T0402	0.120–0.157 (3.05–3.99)
ASNA0341T0403	0.156–0.220 (3.96–5.59)
ASNA0341T0404	0.219–0.282 (5.56–7.16)
ASNA0341T0405	0.281–0.345 (7.14–8.76)
ASNA0341T0406	0.344–0.407 (8.74–10.34)
ASNA0341T0407	0.406–0.470 (10.31–11.94)
ASNA0341T0408	0.469–0.532 (11.91–13.51)
ASNA0341T0409	0.531–0.595 (13.49–15.11)
ASNA0341T0410	0.594–0.656 (15.09–16.67)
ASNA0341T0411	0.656–0.720 (16.66–18.29)
ASNA0341T0412	0.719–0.782 (18.26–19.86)
ASNA0341T0413	0.781–0.845 (19.84–21.46)
ASNA0341T0414	0.844–0.907 (21.44–23.04)

-06 · 3/16 in nominal 16 part numbers

Part no.	Grip, in (mm printed)
ASNA0341T0601	0.093–0.157 (2.36–3.99)
ASNA0341T0602	0.120–0.157 (3.05–3.99)
ASNA0341T0603	0.156–0.220 (3.96–5.59)
ASNA0341T0604	0.219–0.282 (5.56–7.16)
ASNA0341T0605	0.281–0.345 (7.14–8.76)
ASNA0341T0606	0.344–0.407 (8.74–10.34)
ASNA0341T0607	0.406–0.470 (10.31–11.94)
ASNA0341T0608	0.469–0.532 (11.91–13.51)
ASNA0341T0609	0.531–0.595 (13.49–15.11)
ASNA0341T0610	0.594–0.656 (15.09–16.67)
ASNA0341T0611	0.656–0.720 (16.66–18.29)
ASNA0341T0612	0.719–0.782 (18.26–19.86)
ASNA0341T0613	0.781–0.845 (19.84–21.46)
ASNA0341T0614	0.844–0.907 (21.44–23.04)

-05 · 5/32 in nominal 16 part numbers

Part no.	Grip, in (mm printed)
ASNA0341T0501	0.093–0.157 (2.36–3.99)
ASNA0341T0502	0.120–0.157 (3.05–3.99)
ASNA0341T0503	0.156–0.220 (3.96–5.59)
ASNA0341T0504	0.219–0.282 (5.56–7.16)
ASNA0341T0505	0.281–0.345 (7.14–8.76)
ASNA0341T0506	0.344–0.407 (8.74–10.34)
ASNA0341T0507	0.406–0.470 (10.31–11.94)
ASNA0341T0508	0.469–0.532 (11.91–13.51)
ASNA0341T0509	0.531–0.595 (13.49–15.11)
ASNA0341T0510	0.594–0.656 (15.09–16.67)
ASNA0341T0511	0.656–0.720 (16.66–18.29)
ASNA0341T0512	0.719–0.782 (18.26–19.86)
ASNA0341T0513	0.781–0.845 (19.84–21.46)
ASNA0341T0514	0.844–0.907 (21.44–23.04)

-08 · 1/4 in nominal 16 part numbers


Part no.	Grip, in (mm printed)
ASNA0341T0801	0.093–0.157 (2.36–3.99)
ASNA0341T0802	0.120–0.157 (3.05–3.99)
ASNA0341T0803	0.156–0.220 (3.96–5.59)
ASNA0341T0804	0.219–0.282 (5.56–7.16)
ASNA0341T0805	0.281–0.345 (7.14–8.76)
ASNA0341T0806	0.344–0.407 (8.74–10.34)
ASNA0341T0807	0.406–0.470 (10.31–11.94)
ASNA0341T0808	0.469–0.532 (11.91–13.51)
ASNA0341T0809	0.531–0.595 (13.49–15.11)
ASNA0341T0810	0.594–0.656 (15.09–16.67)
ASNA0341T0811	0.656–0.720 (16.66–18.29)
ASNA0341T0812	0.719–0.782 (18.26–19.86)
ASNA0341T0813	0.781–0.845 (19.84–21.46)
ASNA0341T0814	0.844–0.907 (21.44–23.04)

Showing 56 of 64 rows. Complete table: theaviationpoint.com/parts/blind-fasteners/asna0341/

Reference data. The aircraft manufacturer's documentation (SRM / IPC) takes precedence.

THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT · THEAVIATIONPOINT.COM

How to read the part number



Segment	Reads as	Unit of the code · from
ASNA0341 Standard	Blind bolt with pulled stem and locking collar (MAXIBOLT type), titanium. Head: 100° countersunk.	None: the number of the standard · The standard
T Material	Titanium (the standard does not print what the letter stands for)	Letter, no unit · Letter printed by the standard; its meaning is not printed
05 Diameter	5/32 in nominal: 5 × 1/32 in (0.156 in · 3.969 mm, our conversion); body diameter 0.163 in · 4.14 mm; hole 0.164–0.167 in · 4.16–4.24 mm (mm by context); countersink diameter, max 0.334 in · 8.48 mm (mm by context).	1/32 in, by the inch dash logic (the unit of the code is not printed); inch and mm values are our conversion · Diameter and hole table (Dimensions by size, above)
06 Grip	6/16 in = 3/8 in nominal grip; stack 0.344–0.407 in · 8.74–10.34 mm.	1/16 in steps, nominal grip (inch dash logic); the range is printed in mm · Grip table (Part numbers, above)
(none) Option	No letter: standard supply.	Letter, no unit · Procurement letter of the standard

ASNA0341T0506 reads: **ASNA0341** titanium Maxibolt-type blind bolt, 100° countersunk · **T** titanium · **05** 5/32 in, hole 4.16–4.24 mm, drill #19 · **06** 3/8 in, stack 8.74–10.34 mm · option standard supply.

Tools by diameter code

Code	Tool	Straight head	90° head	Offset head
04 (titanium)	G704B or G747	H701B-456 or H747-456	H753A-456	H782 + insert 782-456
05	G83 (or G704B / G747 with the -456 heads)	H83B-5MB	H828-5MB + adapter 744-300	H782 + insert 782-456 + adapter 744-300
06	G83	H83B-6MB	H828-6MB + adapter 744-300	H856-6MB + adapter 744-300
08	G84	H84A-8MB	titanium S only: H828-8MB on G84 + adapter 744-200 (maker's catalogue); none on the standard's sheet	none
U type, 05	as S	H83B-5MBU	H828-5MBU	—
U type, 06	as S	H83B-6MBU	H828-6MB with U nosepiece 828-036	—
U type, 08	as S	H84A-8MBU, H84C-8MBU, H84D-8MBU	—	—

From the standards' tooling table and the maker's pulling-head sheets. U-type heads and the titanium -8 head are the maker's catalogue. The G746A is recommended only for Maxibolt -4 and -5.

Inspection limits

Check	Limit, inch first
Gap under the head	Not more than 0.004 in (0.10 mm, printed in mm). Protruding head: on no more than 10 % of the row and never on 2 consecutive fasteners. Countersunk head: over no more than half the periphery, on no more than 20 % of the row, never on 2 consecutive
Countersunk head flush	Ideal 0; accepted +0.05 / −0.10. Unit not stated (the other tolerances on the sheet are mm): not converted
Stem flush B (on the break)	code 04: ±0.010 in (±0.25 mm); code 05: ±0.010 in (±0.25 mm); code 06: ±0.010 in (±0.25 mm); code 08: ±0.015 in (±0.38 mm). Millimetres printed and stated
Collar flush A (never proud)	code 04: 0 / −0.015 in (−0.38 mm); code 05: 0 / −0.017 in (−0.43 mm); code 06: 0 / −0.022 in (−0.56 mm); code 08: 0 / −0.029 in (−0.74 mm). Millimetres printed and stated
Collar	Must never stand beyond the stem after the break; check that it is present

Limits as the standard gives them; the aircraft's SRM governs.

Notes

- Part number: ASNA0341 + material letter T + diameter code (04, 05, 06 or 08) + grip code (01 to 16) + optional R.
- The standard does not print what the letter T stands for; it is read as titanium. Grip rows 01 (0.093–0.157 in) and 02 (0.120–0.157 in) overlap and carry no diameter label. Stem heads carry three marks: material left, maker top, grip lower right.
- The body is bigger than the nominal fraction: code 05 is 5/32 in nominal (0.156 in) but 0.163 in at the body, and the hole is 0.164–0.167 in. Drill from the hole table, never from the nominal.
- Countersunk head: do not deburr the hole edge; countersink up to the largest diameter of the table. The countersink never goes through the sheet: a straight bore of at least 0.008 in (0.2 mm, printed in mm) remains.
- The Maxibolt grip code n is shifted 1/32 in against the Cherry-type codes (code 04 is 0.219–0.282 in here, 0.188–0.250 in on CherryMAX). Lengths in work documents are indicative: measure the stack with a grip gauge.
- Units: no mark = printed in mm and stated by the standard. † = printed with no unit; the inch value is our conversion, reading the figure as mm. Nominal Ø is our reading of the inch code (1/32 in for diameters, 1/16 in for grips). Drill: from the site drill chart, inside the hole range except code 04, where the chart's #30 (0.1285 in) is just under the printed minimum (a drill cuts slightly oversize): gauge the finished hole.

SOURCES · ASNA0341 standard · Cherry Aerospace pulling-head sheets · US federal item records and distributor listings

SCAN · OPEN THIS DATA SHEET
theaviationpoint.com/parts/blind-fasteners/asna0341/

Reference data. The aircraft manufacturer's documentation (SRM / IPC) takes precedence.