THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT · THEAVIATIONPOINT.COM

ATS-114C-30 — pneumatic C squeezer with 3 in yoke

The ATS pneumatic C squeezer, from the ATS product page.

Specification

Item	Value
Type	Pneumatic C squeezer
Supplied with	3 in yoke (p/n 14-7), adjustable ram (p/n 214CAR)
Accepts	All squeezer and dimpling sets with a .187 in shank
Compatible with	Chicago Pneumatic 0214-C squeezers: same yokes and attachments
Status	Maker's published figures, read 30 October 2026. Confirm with the maker before relying on one.

Dimensions by size

Dimension	ATS-114C-30
Length	10 in (254.0 mm)
Yoke	3 in (76.2 mm)
Rivet capacity, aluminum or steel	1/8 in (3.18 mm)
Set shank	.187 in (4.75 mm)

Inches as published are the official values. Millimetres are converted at 25.4 mm per inch and are not official.

Part numbers

Part no.	Size	Force	Shipping weight, lb
ATS-114C-30	3 in yoke	3000 lb at 90 psi	6

Model as the source lists it. Shipping weight is the page's figure for the boxed item, not the tool's own weight, which the page does not give.

Notes

- ATS says it based this squeezer on the Chicago Pneumatic 0214-C, with the same power.
- The feature list gives 1/8 in aluminum or steel rivets; the description says solid aluminum or mild steel.

SOURCES · ATS-114C-30 — ATS Pro Pneumatic C Squeezer, product page

SCAN · OPEN THIS DATA SHEET
theaviationpoint.com/parts/tools/ats-114c-30/

Reference data. The aircraft manufacturer's documentation (SRM / IPC) takes precedence.