THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT

H84A-8 — straight pulling head for CherryMAX blind fasteners

Straight Pulling Head, -8 CherryMAX.

Specification

Item	Value
Type	Straight pulling head
Maker	Cherry Aerospace
Weight	0.2 lb (0.09 kg)
Tool sheet	TS-H84A-8, Rev. C, 11-30-09

Part numbers

Part no.	Size
H84A-8	1/4 in (-8)

Cherry's part numbers on this tool sheet.

What it installs as supplied

Fastener	Diameter
CherryMAX blind fasteners	8

Riveters

Riveter	Adapter	Note
G84	—	
G84-LS	744-700	Split Power Riveter

Parts list

Item	Part number	Description	Qty
1	749B53	NOSE PIECE	1
2	652-005	SLEEVE	1
3	652-030	COLLET	1
4	563C35	JAW SET	1
5	652-042	JAW FOLLOWER	1
6	P-1462	COMPRESSION SPRING	1

Notes

- Mounting: attach riveter to air source; thread collet assembly securely onto riveter head piston; depress trigger and attach sleeve assembly onto bayonet mount.
- If stem slippage occurs, clean or replace jaws.
- Clean nose piece, jaw set and collet every 1,000 installations or when failures occur. Lubricate outside of jaw set with Lubriplate or similar light lubricant. Replace worn or broken components.

SOURCES · Cherry Aerospace, Tool Sheet TS-H84A-8, Rev. C, 11-30-09

SCAN · OPEN THIS DATA SHEET
theaviationpoint.com/parts/tools/h84a-8/

Reference data. The aircraft manufacturer's documentation (SRM / IPC) takes precedence.