
THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT

HL70 collar — shear, aluminum alloy

Hi-Lok Collar, Shear, Aluminum Alloy: dimensions by size, strength and torque-off.



HL70



Engineering drawing · dimensions in inches

Specification

Item	Value
Type	Hi-Lok collar, shear
Material	2024-T6 aluminum alloy
Strength	Shear application
Status	Check the current issue before design use.

Dimensions by size

Dimension, in	8-32UNJC-3B	10-32UNJF-3B	1/4-28UNJF-3B	5/16-24UNJF-3B
Pin nominal diameter	5/32	3/16	1/4	5/16
A — Collar diameter (max / min)	.292 - .288	.307 - .303	.412 - .408	.518 - .512
B — Bore diameter (max / min)	.173 - .166	.200 - .192	.261 - .252	.325 - .314
L — Length	.447 - .427	.457 - .437	.552 - .532	.672 - .652
Thread	8-32UNJC-3B	10-32UNJF-3B	1/4-28UNJF-3B	5/16-24UNJF-3B
Collar UTS, lb min	1,400	1,600	3,000	5,000
Torque-off, in-lb	15-25	25-35	60-80	130-160

Dimensions as tabulated in the catalogue, by dash number (pin nominal diameter). Max - min where a tolerance is shown.

Part numbers

Part no.	Size	Torque-off, in-lb
HL70-5	5/32	15-25
HL70-6	3/16	25-35
HL70-8	1/4	60-80
HL70-10	5/16	130-160

Every collar dash number listed, by pin diameter.

How to read the part number

Part	Meaning
Format	HL70-<dash>
Example	HL70-5 — 5/32 nominal pin diameter

Notes

- Max - min values shown as max - min. Approved data governs.
- Pins this collar is listed for in the catalogue: HL18, HL19 (standard collar).

SOURCES · HL70 — Hi-Lok Collar, Shear, Aluminum Alloy

SCAN · OPEN THIS DATA SHEET
theaviationpoint.com/parts/hi-lok/hl70/