THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT

MS51831 — heavy-duty key-locked insert

Insert, Heavy Duty, Locked In, Key Locked, Corrosion-Resistant Steel: part numbers and the sizes commonly stocked.



MS51831

Specification

Item	Value
Type	Threaded insert, key locked
Material	Corrosion-resistant steel; A in place of the dash: alloy steel
Status	Check the current issue before design use.

Part numbers

Part no.	Size	External thread	Length, in	Locking tabs
MS51831-201	.1900-32	.3750-16	.312	2
MS51831-201L	.1900-32	.3750-16	.312	2
MS51831A201L	.1900-32	.3750-16	.312	2
MS51831-202	.2500-28	.4375-14	.375	2
MS51831-202L	.2500-28	.4375-14	.375	2
MS51831-203L	.3125-24	.5000-13	.437	4
MS51831-204L	.3750-24	.5625-12	.500	4

Part numbers commonly stocked. The standard governs and may list others.

How to read the part number

Part	Meaning
A	Letter: In place of the dash: alloy steel
L	Letter: After the dash number: internal thread lock
Example	MS51831-201 — Internal thread .1900-32, external .3750-16

Notes

- The size column is the internal thread. A in place of the dash indicates alloy steel; L after the dash number indicates an internal thread lock.
- The listing names NAS1395 as the alternate number.

SOURCES · MS51831 — Insert, Heavy Duty, Locked In, Key Locked, Corrosion-Resistant Steel

SCAN · OPEN THIS DATA SHEET
theaviationpoint.com/parts/inserts/ms51831/