THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT

NAS548 screw — 100° flat countersunk, tapping

Screw, Tapping, 100° Flat Head: thread sizes, lengths and commonly stocked part numbers.



NAS548

Specification

Item	Value
Head	100° flat countersunk, tapping
Drive	cross recess
Status	Check the current issue before design use.

Part numbers and lengths

No. 4 3 part numbers

Part no.	Length, in
NAS548P4-4	1/4
NAS548P4-6	3/8
NAS548P4-8	1/2

No. 6 4 part numbers

Part no.	Length, in
NAS548P6-6	3/8
NAS548P6-8	1/2
NAS548P6-10	5/8
NAS548P6-12	3/4

No. 8 4 part numbers

Part no.	Length, in
NAS548P8-6	3/8
NAS548P8-8	1/2
NAS548P8-10	5/8
NAS548P8-12	3/4

No. 10 4 part numbers

Part no.	Length, in
NAS548P10-6	3/8
NAS548P10-8	1/2
NAS548P10-10	5/8
NAS548P10-12	3/4

Notes

- Listed as NAS548P (cadmium Type I plating on the listing). Dash number: size, then length in sixteenths of an inch.
- The listing sets it beside MS21207 with the same size and length.
- Part number written as the listing writes it; the standard governs the exact format.
- Approved data governs. Use the screw the SRM, drawing or IPC calls for.

SOURCES · NAS548 — Screw, Tapping, 100° Flat Head

SCAN · OPEN THIS DATA SHEET
theaviationpoint.com/parts/screws/nas548/