
THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT

NAS6408 — hex head close tolerance, titanium, aluminum coated

Bolt, Hexagon Head, Close Tolerance, Titanium 6Al-4V, Aluminum Coated: thread, grip, length and commonly stocked part numbers.



NAS6408



Engineering drawing · dimensions in inches

Specification

Item	Value
Type	Close tolerance bolt
Material	Titanium alloy 6Al-4V, aluminum coated
Strength	Ultimate tensile 160-180 ksi, ultimate shear 95 ksi min
Status	Check the current issue before design use.

Part numbers

Dash 2 part numbers

Part no.
NAS6408A17D
NAS6408A84

Notes

- D indicates aluminum.
- The listing gives stock part numbers only: grip and length are not stated.
- Part number format as commonly written; check the standard for the exact format.
- Approved data governs. Use the bolt the SRM, drawing or IPC calls for.

SOURCES · NAS6408 — Bolt, Hexagon Head, Close Tolerance, Titanium 6Al-4V, Aluminum Coated

SCAN · OPEN THIS DATA SHEET
theaviationpoint.com/parts/structural-bolts/nas6408/