THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT · THEAVIATIONPOINT.COM

The Aviation Point

PE21101-3 screw — 130° flat countersunk

Screw, 130° Flat Head, Torq-Set Recess, 10-32: thread sizes, lengths and commonly stocked part numbers.



PE21101-3

Specification

Item	Value
Head	130° flat countersunk
Drive	Torq-Set recess
Status	Check the current issue before design use.

Part numbers and lengths

10-32 11 part numbers

Part no.	Length, in	Grip, in
PE21101-3-1SD	13/32	—
PE21101-3-2CP	15/32	1/8
PE21101-3-2SD	15/32	1/8
PE21101-3-3CP	17/32	3/16
PE21101-3-3SD	17/32	3/16
PE21101-3-4CP	19/32	1/4
PE21101-3-4SD	19/32	1/4
PE21101-3-6CP	23/32	3/8
PE21101-3-6SD	23/32	3/8
PE21101-3-8SD	27/32	1/2
PE21101-3-10SD	—	5/8

Notes

- Letters after the dash number: S, steel alloy; D, cadmium-plated steel alloy; C, corrosion-resistant steel; P, passivated corrosion-resistant steel.
- Grip of -1SD is printed illegibly in the listing; it is left blank.
- Part number written as the listing writes it; the standard governs the exact format.
- Approved data governs. Use the screw the SRM, drawing or IPC calls for.
- Length of PE21101-3-10SD is left blank: the listed length does not follow the length-grip pattern of the series. Confirm against the standard.

SOURCES · PE21101-3 — Screw, 130° Flat Head, Torq-Set Recess, 10-32

SCAN · OPEN THIS DATA SHEET
theaviationpoint.com/parts/screws/pe21101-3/

Reference data. The aircraft manufacturer's documentation (SRM / IPC) takes precedence.