
THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT · THEAVIATIONPOINT.COM

The Aviation Point

PR-1776M — polysulfide sealant

Polysulfide is the classic aircraft sealant: two parts mixed, cured at room temperature to a flexible fuel-resistant rubber.



Schematic

Designation

Item	Value
Designation	PR-1776M
Class	Sealants
Type	polysulfide sealant

Data from the guide

Item	Value
Product	PR-1776M Class B
Maker	PPG
Form and class	Two-part, manganese dioxide cured, Permapol P-5 modified polysulfide (PPG's wording)
Life and cure (from the source)	B-1/2, B-2 grades
Specification stated	AMS 3281 Type 1 Class B-2; BMS 5-45

Sources: PPG PR-1422 sheet (09/10); distributor listings for PS-890 and PR-1440; PPG PR-1776M page; Flamemaster CS 3201 bulletin. Distributor lists are not PPG data sheets.

Notes

- **Distributor lists** for PR-1440 and PS-890: they are not PPG data sheets.
- **No cross-reference table is authoritative.** The SRM and the specification's QPL decide equivalents.
- **Specifications are cited as the sources print them.** AMS-S-8802 text is paid and was not read.

SOURCES · PPG Aerospace, PR-1422 Class B Fuel Tank Sealant, data sheet · Flamemaster Corporation, Chem Seal CS 3201 Technical Bulletin · PPG PS890 B-1/2 Fuel Tank Sealant · PPG PR-1440 B-1/2 Fuel Tank Sealant · PPG Aerospace, PR-1776M Class B Low Weight Fuel Tank Sealant, PPG PR1776M B-2 Low Weight Fuel Tank Sealant · Sealant application bulletin: class and applications · SAE International, AS5127/1C: Test Methods for Aerospace Sealants, Two-Component Synthetic Rubber Compounds

SCAN · OPEN THIS DATA SHEET
theaviationpoint.com/parts/materials/pr-1776m/

THE AVIATION POINT · THEAVIATIONPOINT.COM · THE AVIATION POINT · THEAVIATIONPOINT.COM